













Product Overview

(Intelligent Systems for Solids)



		Application Field (online and continuous)	Selection / Distinction
	FlowJam	Flow / No-Flow Control	
	ProGap II	Level Detection	
	Solidflow	Measurement of flow rate	<ul style="list-style-type: none"> - in delute-phased material flow - free fall and pneumatic transport - up to ca. 20 t/h
	DensFlow	Measurement of flow rate	<ul style="list-style-type: none"> - in dense-phased material flow
	MaxxFLOW	Measurement of flow rate	<ul style="list-style-type: none"> - in delute-phased material flow - in free fall and sloping pipe - from ca. 20 t/h
	SlideControl	Measurement of flow rate	<ul style="list-style-type: none"> - in air slides
	ClampFlow	Measurement of flow rate	<ul style="list-style-type: none"> - in flexible tubes (non-metalliferous) - in delute- and dense-phased material flow - free fall and pneumatic transport
	SpeedFlow	Measurement of velocity	
	M-Sens 2	Measurement of moisture	
	Dens-M	Measurement of bulk density	
	ProSens	1. Broken Bag Detection	<p>Compared to "Dusty"</p> <ul style="list-style-type: none"> - also at high temperatures beyond 140 °C - also at high EX-zones beyond cat. 3 GD
		2. Trend Monitoring	
		3. Emission Measurement	
	Dusty	1. Broken Bag Detection	<p>Compared to "FlowJam"</p> <p>Using at very low flow rates</p>
		2. Flow / No-Flow Control	